



COVELITE EXTERIOR



Applications

Integration into building façades of continuous halo effects.

Description

The **acdc** Covelite system has been used throughout the world for interior coffer lighting applications, uplighting ceilings and features with smooth continuous light whilst eliminating unattractive hot spots and shadow gaps.

Covelite Exterior is an exterior rated version of the same modular product, utilising the same long life cold cathode lamp, and IP65 high frequency control gear mounted on an aluminium gear tray. The quick fit modular units can be easily installed using IP65 plug and sockets making this a simple yet effective exterior lighting solution.

Features

- IP65 for exterior use
- Fully modular solution
- Simple IP plug and socket
- Compact 80mm square profile
- Low weight
- Curved or straight
- No fireman's switch required

Gear Mounting Position

- Integral

NB: This product is designed for indirect lighting applications. Superior quality metalwork can be provided, and painted to RAL colours. For further assistance contact sales.


Benefits

Covelite Exterior offers the following additional benefits:

- **Easy to Specify:** Covelite gives the designer known parameters to work with in terms of lighting performance, dimensions and power consumption. It is as easy to specify as any standard lighting product.
- **Easy to Install:** This plug and socket arrangement minimises installation time. Loop in and out mains connections using IP65 plug and sockets.

Technical Data

Please note that all dimensions are subject to a tolerance of +/- 2mm




Single Run

Minimum:

H = 60mm W = 60mm

Typical:

H = 80mm W = 80mm



Twin Run

Minimum:

H = 80mm W = 80mm

Typical:

H = 80mm W = 80mm

NB: For curved runs allow typical dimensions.